




Damp2Dry[®] COMMERCIAL DEHUMIDIFIER

250 PINT



1PACD250	
UPC CODE	842149026103
WATER REMOVAL CAPACITY (90°F, 90% RH)	250 pts./Day (31.25 gal./Day)
WATER REMOVAL CAPACITY (80°F, 60% RH)	142 pts./Day (17.75 gal./Day)
RATED POWER (W)	1,180
RATED CURRENT (A)	10.4
DEFROST TYPE	Hot Gas Bypass
AIR VOLUME (CFM)	450
OPERATING TEMPERATURE	33°F - 100°F
REFRIGERANT	R410A
WASHABLE AIR FILTER	Yes
POWER CORD LENGTH (ft.)	9.75
DRAIN HOSE LENGTH (ft.)	39
UNIT DIMENSIONS (W×H×D) (in.)	21 × 38 × 22
PKG. DIMENSIONS (W×H×D) (in.)	24 × 40.5 × 25
STUFFING QTY. (20'/40'/40' HQ)	54 / 114 / 114
WEIGHT (Net/Gross) (lbs.)	137 / 146
OUTLET CONFIGURATION	 15A - 115V



PUMPS WATER
16 FT. VERTICALLY



HIGH RATE OF
WATER REMOVAL



AUTOMATIC
DEFROST



HEAVY DUTY
"NEVER FLAT" TIRES



PACDH16LG (sold separately)
16' vent hose used to direct the heated exhaust air and assist in water evaporation

FEATURES

- Durable polyethylene housing and fixed metal handle
- Direct-to-drain hose access with 39 ft. ejector pump hose
- Low temperature operation down to 33 degrees
- Automatic Defrost prevents evaporator from freezing (hot gas bypass)
- Digital, soft-touch control pad
- Easy-access slide-out washable filter
- Built-in duct attachment ring for connecting a vent hose (sold separately)
- Ideal for any area affected by humidity from flooding, water leakage, or natural disasters

STACKABLE!

