



AIR CONDITIONER

11,600 BTU WINDOW AC WITH HEAT PUMP



WINDOW AC FEATURES

- Electronic controls
- Full range air direction control
- Temperature output range of 61°F–86°F (16°C–30°C)
- Auto Fan, Sleep & Energy Saver modes
- Full function remote control
- 24-hour timer
- Window mounting kit
- Auto restart function
- Slide-out filter access


2PAHP12002

w/ heat pump

CHOOSING

THE RIGHT SIZE AIR CONDITIONER FOR YOUR ROOM


1 MEASURE AREA OF THE ROOM



2 MATCH ROOM SIZE WITH CORRECT BTUs

ROOM SIZE (sq. ft.)	BTUs	
150	10' x 15'	5,000
250	15.5' x 16'	6,000
350	17.5' x 20'	8,000
450	18' x 25'	10,000
550	22' x 25'	12,000
700	25' x 28'	15,000
1,000	31.25' x 32'	18,000
1,500	37.5' x 40'	25,000
2,000	40' x 50'	28,500

3 CONFIRM WINDOW OPENING SIZE



4 CHECK ELECTRICAL REQUIREMENTS

OUTLET CONFIGURATIONS

DETERMINE IF YOUR CIRCUIT IS ADEQUATE

UPC CODE	8-42149-02677-6
COOLING CAPACITY (BTU)	11,600/11,200
HEATING CAPACITY (BTU)	10,200/9,900
COVERAGE (sq. ft.)	450–550
EER	9.9
ENERGY STAR RATED	No
FAN SPEEDS (Cool/Fan/Heat)	3/3/3
AMPS (Cool)	5.3/5.1
AMPS (Heat Pump)	5.3/5.1
AMPS (Electric Heat)	16.0
WATTS (Cool)	1,170/1,130
WATTS (Heat)	1,150/1,110
WATTS (Electric Heat)	3,580/2,770
DECIBELS (Hi/Mi/Lo)	62/60/58
WINDOW WIDTH (Min./Max.) (in.)	27/39
WINDOW HEIGHT (Min.) (in.)	16.25
UNIT DIMENSIONS (WxHxD) (in.)	22 ^{3/4} x 15 ^{1/2} x 23 ^{3/4}
PKG. DIMENSIONS (WxHxD) (in.)	26 x 17 ^{1/4} x 27 ^{1/2}
STUFFING QTY. (20/40/40' HQ)	120/270/324
WEIGHT (Net/Gross) (lbs.)	97/110
REFRIGERATION	R410A
OUTLET CONFIGURATION	20 AMP 230V



PA/Flyer_2PAHP12002/07282017

5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us