



DEHUMIDIFIER

70 PINT



DEHUMIDIFIER FEATURES

- Direct-to-drain hose access
- Easy access bucket with handle
- Bucket full indicator
- Adjustable humidistat
- Washable filter
- Automatic defrost control
- Auto shut-off/restart
- Timer function
- Water level window
- Comfort option: Unit controls humidity based on room temperature
- Side exhaust
- Check filter light

BUCKET W/ HANDLE




WASHABLE FILTER



ELECTRONIC CONTROLS



4PAD70	
UPC CODE	8-42149-02640-0
CAPACITY (pts./Day)	70
COVERAGE (sq. ft.)	4,500
EER	2.0
FAN SPEEDS	2
AMPS	6.5
WATTS	690
DECIBELS (Hi/Lo)	55/54
BUCKET CAPACITY (pts.)	12.7
UNIT DIMENSIONS (WxHxD) (in.)	15 ¹ / ₂ x 23 ¹ / ₄ x 11
PKG. DIMENSIONS (WxHxD) (in.)	16 ³ / ₄ x 24 ¹ / ₄ x 12 ¹ / ₄
STUFFING QTY (20'/40'/40' HQ)	303/624/832
WEIGHT (Net/Gross) (lbs.)	40/44
MIN. OPERATING TEMP	41°F
REFRIGERATION	R410A
OUTLET CONFIGURATION	 15 AMP 115V



PA/SS_4PAD70/05302017

5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us