



DEHUMIDIFIER

95 PINT WITH AUTOMATIC EJECTOR PUMP




DEHUMIDIFIER FEATURES

- Direct-to-drain hose access
- Easy access bucket with handle
- Water level window & bucket full indicator
- Adjustable humidistat
- Washable filter
- Automatic defrost control
- Auto shut-off/restart
- Timer function
- Built-in pump
- Comfort option: Unit controls humidity based on room temperature
- Top exhaust
- Check filter light
- Ion air purifying option

DIRECT-TO-DRAIN




WASHABLE FILTER



ELECTRONIC CONTROLS



	4PADP95
UPC CODE	8-42149-02735-3
CAPACITY (pts./Day)	95
COVERAGE (sq. ft.)	6,000
EER	2.8
ENERGY STAR RATED	No
FAN SPEEDS	2
AMPS	6.8
WATTS	680
DECIBELS (Hi/Lo)	58/56
BUCKET CAPACITY (pts.)	21.1
UNIT DIMENSIONS (WxHxD) (in.)	19 x 24 ^{3/4} x 14 ^{1/4}
PKG. DIMENSIONS (WxHxD) (in.)	20 ^{1/2} x 26 x 16 ^{1/4}
STUFFING QTY (20'/40'/40' HQ)	183/381/507
WEIGHT (Net/Gross) (lbs.)	61/64
MIN. OPERATING TEMP	41°F
REFRIGERATION	R410A
OUTLET CONFIGURATION	 15 AMP 115V



PA/SS_4PADP95/02122018

5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us