



# AIR CONDITIONER

## 12,000 BTU THRU-THE-WALL AC



**FOLLOW ME**  
Portable remote control thermostat feature for total room coverage


### THRU-THE-WALL AC FEATURES

- Electronic controls
- Full range air direction control
- Temperature output range of 62°F–86°F (17°C–30°C)
- Auto, Sleep, Dry & Energy Saver modes
- Full function remote control
- 24 hour timer
- Auto restart function
- Slide-out filter access

### CHOOSING

THE RIGHT SIZE AIR CONDITIONER FOR YOUR ROOM


#### 1 MEASURE AREA OF THE ROOM




#### 2 MATCH ROOM SIZE WITH CORRECT BTUs

ROOM SIZE (sq. ft.)	BTUs	
150	10' x 15'	5,000
250	15.5' x 16'	6,000
350	17.5' x 20'	8,000
450	18' x 25'	10,000
550	22' x 25'	12,000
700	25' x 28'	15,000
1,000	31.25' x 32'	18,000
1,500	37.5' x 40'	25,000
2,000	40' x 50'	28,500


#### 3 CONFIRM WALL OPENING SIZE



#### 4 CHECK ELECTRICAL REQUIREMENTS



#### 4PATW12002

UPC CODE	8-42149-02568-7
COOLING CAPACITY (BTU)	12,000/11,700
COVERAGE (sq. ft.)	450–550
EER	10.5
ENERGY STAR RATED	Yes
FAN SPEEDS (Cool/Fan)	3/3
AMPS	5.2/5.6
WATTS	1,142/1,114
DECIBELS (Hi/Mi/Lo)	61/59/57
INTERIOR TRIM KIT INCLUDED	Yes
FITS STANDARD WALL SLEEVES	Yes (sold separately)
UNIT DIMENSIONS (WxHxD) (in.)	24 <sup>1/4</sup> x 14 <sup>1/2</sup> x 20 <sup>1/2</sup>
PKG. DIMENSIONS (WxHxD) (in.)	28 x 17 x 26 <sup>3/4</sup>
STUFFING QTY. (20'/40'/40' HQ)	120/255/306
WEIGHT (Net/Gross) (lbs.)	78/89
REFRIGERATION	R410A
OUTLET CONFIGURATION	 15 AMP 230V



PA/SS\_4PATW12002/11292017

5401 Dansher Road  
Countryside, IL 60525

866.996.9255  
630.323.2301

www.perfectaire.us  
support@perfectaire.us