



DEHUMIDIFIER

50 PINT EJECTOR PUMP



DIRECT-TO-DRAIN



EJECTOR PUMP




ELECTRONIC CONTROLS



DEHUMIDIFIER FEATURES

- Easy access bucket with handle
- Bucket full indicator
- Adjustable humidistat
- Washable filter
- Automatic defrost control
- Auto shut-off/restart
- Timer function
- Water level window
- Side exhaust
- Built-in pump
- Optional continuous 6 foot drainage

		1PEDP50
UPC CODE		8-42149-02636-3
CAPACITY (pts./Day)		50
COVERAGE (sq. ft.)		3,000
EER		2.0
FAN SPEEDS		2
AMPS		4.7
WATTS		535
DECIBELS (Hi/Lo)		54/53
BUCKET CAPACITY (pts.)		18.8
UNIT DIMENSIONS (WxHxD) (in.)		15 ^{1/2} x 23 ^{3/4} x 11 ^{1/4}
PKG. DIMENSIONS (WxHxD) (in.)		16 ^{3/4} x 24 ^{1/4} x 12 ^{1/2}
STUFFING QTY (20'/40'/40' HQ)		303/624/832
WEIGHT (Net/Gross) (lbs.)		38/41
MIN. OPERATING TEMP		41°F
REFRIGERATION		R410A
OUTLET CONFIGURATION		 15 AMP 115V



PA/SS_1PEDP50/05302017

5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us