



DEHUMIDIFIER

70 PINT EJECTOR PUMP



DIRECT-TO-DRAIN



EJECTOR PUMP




ELECTRONIC CONTROLS



DEHUMIDIFIER FEATURES

- Easy access bucket with handle
- Bucket full indicator
- Adjustable humidistat
- Washable filter
- Automatic defrost control
- Auto shut-off/restart
- Timer function
- Water level window
- Side exhaust
- Built-in pump
- Optional continuous 6 foot drainage

	1PEDP70
UPC CODE	8-42149-02637-0
CAPACITY (pts./Day)	70
COVERAGE (sq. ft.)	4,500
EER	2.0
FAN SPEEDS	2
AMPS	7.5
WATTS	720
DECIBELS (Hi/Lo)	56/55
BUCKET CAPACITY (pts.)	18.8
UNIT DIMENSIONS (WxHxD) (in.)	15 ^{1/2} x 23 ^{3/4} x 11 ^{1/4}
PKG. DIMENSIONS (WxHxD) (in.)	16 ^{3/4} x 24 ^{1/4} x 12 ^{1/2}
STUFFING QTY (20'/40'/40' HQ)	303/624/832
WEIGHT (Net/Gross) (lbs.)	45/49
MIN. OPERATING TEMP	41°F
REFRIGERATION	R410A
OUTLET CONFIGURATION	 15 AMP 115V



PA/SS_1PEDP70/05302017

5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us