




Damp2Dry[®] COMMERCIAL DEHUMIDIFIER

150 PINT



| 1PACD150 | |
|---------------------------------------|---|
| UPC CODE | 842149025250 |
| WATER REMOVAL CAPACITY (90°F, 90% RH) | 150 pts./Day (18.75 gal./Day) |
| WATER REMOVAL CAPACITY (80°F, 60% RH) | 76 pts./Day (9.5 gal./Day) |
| RATED POWER (W) | 810 |
| RATED CURRENT (A) | 7.3 |
| DEFROST TYPE | Hot Gas Bypass |
| AIR VOLUME (CFM) | 235 |
| OPERATING TEMPERATURE | 33°F - 100°F |
| REFRIGERANT | R410A |
| WASHABLE AIR FILTER | Yes |
| POWER CORD LENGTH (ft.) | 9.75 |
| DRAIN HOSE LENGTH (ft.) | 39 |
| UNIT DIMENSIONS (W×H×D) (in.) | 20 × 32 × 19 |
| PKG. DIMENSIONS (W×H×D) (in.) | 22 × 34 × 21 |
| STUFFING QTY. (20'/40'/40' HQ) | 80 / 176 / 260 |
| WEIGHT (Net/Gross) (lbs.) | 81 / 90 |
| OUTLET CONFIGURATION |  15A - 115V |



PUMPS WATER
16 FT. VERTICALLY



HIGH RATE OF
WATER REMOVAL



AUTOMATIC
DEFROST



HEAVY DUTY
"NEVER FLAT" TIRES



PACDH16SM (sold separately)
16' vent hose used to direct the heated exhaust air and assist in water evaporation

FEATURES

- Durable polyethylene housing and fixed metal handle
- Direct-to-drain hose access with 39 ft. ejector pump hose
- Low temperature operation down to 33 degrees
- Automatic Defrost prevents evaporator from freezing (hot gas bypass)
- Digital, soft-touch control pad
- Easy-access slide-out washable filter
- Built-in duct attachment ring for connecting a vent hose (sold separately)
- Ideal for any area affected by humidity from flooding, water leakage, or natural disasters