




Damp2Dry[®] COMMERCIAL DEHUMIDIFIER

200 PINT



2PACD200	
UPC CODE	842149025786
WATER REMOVAL CAPACITY (90°F, 90% RH)	200 pts./Day (25 gal./Day)
WATER REMOVAL CAPACITY (80°F, 60% RH)	105 pts./Day (13 gal./Day)
RATED POWER (W)	860
RATED CURRENT (A)	7.5
DEFROST TYPE	Hot Gas Bypass
AIR VOLUME (CFM)	410
OPERATING TEMPERATURE	33°F - 100°F
REFRIGERANT	R410A
WASHABLE AIR FILTER	Yes
POWER CORD LENGTH (ft.)	9.75
DRAIN HOSE LENGTH (ft.)	39
UNIT DIMENSIONS (W×H×D) (in.)	21 × 32.5 × 20
PKG. DIMENSIONS (W×H×D) (in.)	23.5 × 35 × 22
STUFFING QTY. (20'/40'/40' HQ)	72 / 152 / 228
WEIGHT (Net/Gross) (lbs.)	97 / 106
OUTLET CONFIGURATION	 15A - 115V

- 

**PUMPS WATER
16 FT. VERTICALLY**
- 

**HIGH RATE OF
WATER REMOVAL**
- 


**AUTOMATIC
DEFROST**
- 

**HEAVY DUTY
"NEVER FLAT" TIRES**

FEATURES

- Durable polyethylene housing and fixed metal handle
- Direct-to-drain hose access with 39 ft. ejector pump hose
- Low temperature operation down to 33 degrees
- Automatic Defrost prevents evaporator from freezing (hot gas bypass)
- Digital, soft-touch control pad
- Easy-access slide-out washable filter
- Built-in duct attachment ring for connecting a vent hose *(sold separately)*
- Ideal for any area affected by humidity from flooding, water leakage, or natural disasters





PACDH16SM *(sold separately)*
16' vent hose used to direct the heated exhaust air and assist in water evaporation