



DEHUMIDIFIER

50-PINT, 60-PINT WITH PUMP



2PFDP50



1PDP60



BUILT-IN PUMP
Continuous vertical drainage up to 16' away



ADJUSTABLE DIGITAL HUMIDISTAT
Provides precise humidity control



AUTOMATIC DEFROST
prevents evaporator from freezing



AUTOMATIC SHUT OFF
when bucket is full

2PFDP50

1PDP60

	2PFDP50	1PDP60
UPC	8-42149-09013-5	8-42149-09126-2
CAPACITY (PTS./DAY)	50	60
COVERAGE (SQ. FT.)	4,500	5,000
EER	1.9	2.8
FAN SPEEDS	2	2
AMPS	4.8	4.1
WATTS	515	420
DECIBELS (HI/LO)	51/49	59/55
BUCKET CAPACITY (PTS.)	12.7	21
UNIT DIMENSIONS (WxHxD) (IN.)	15.5 x 24.25 x 11	14.25 x 24.75 x 19
PKG. DIMENSIONS (WxHxD) (IN.)	17 x 26 x 13	16.25 x 26 x 20.5
STUFFING QTY. (20'/40'/40' HQ)	288/582/775	183/381/508
WEIGHT (NET/GROSS) (LBS.)	43/46	58/63
MIN. OPERATING TEMP	41°F	41°F
REFRIGERANT	R410A	R410A

OUTLET CONFIGURATION



15 AMP 115V



15 AMP 115V

FEATURES

- 60-pint capacity dehumidifier covers small spaces up to 5,000 sq. ft.
- Sleek, flat panel design with soft touch electronic control pad
- Comfort option: Unit controls humidity based on room temperature
- Reusable, washable air filter
- Environmentally friendly, non-ozone depleting R410A refrigerant
- Minimum operating temperature of 41°F (5°C)
- Direct-to-drain feature allows for continuous operation (hose not included)
- Water level window

PA/SS_2PFDP50_1PDP60/12022020